




# DRVO-ALUMINIJ PROZORI



**Premier Classic**  
DALU 68 mm

**Premier Termic**  
DALU 68 mm

**Premier Plus**  
DALU 68 mm

**Premier Flat**  
DALU 68 mm

**Premier Zero**  
DALU 68 mm

**Premier Passiv**  
DALU 80 mm

**Premier Passiv Modern**  
DALU 80 mm

Dimenzije profila (mm)	Ugrađena debljina profila	82	78	78	78,5	78,5	93,5	110
	Vidljiva širina profila	125	125	122	125	118	125	125
	Vidljiva širina kemfera/MITLINA (2 krila)	80	80	✗	✗	80	80	80
Oblici izvedbe	Pravokutni	✓	✓	✓	✓	✓	✓	✓
	Kosi	✓	✓	✗	✓	✓	✓	✓
	Polukružni, kružni	✓	✓	✗	✓	✗	✗	✗
Načini otvaranja	Fiksno	✓	✓	✓	✓	✓	✓	✓
	Oz/z	✓	✓	✓	✓	✓	✓	✓
	Podizno klizne stijene	✓	✓	✗	ZERO	✓	/	/
	Otklopno klizne stijene	✓	✓	✓	✓	✓	/	/
	Harmo stijene	✓	✓	✓	✓	✓	/	/
	Vrata na zaključavanje	✓	✓	✓	✓	✗	/	/
	Vrata s otvaranjem prema van	✓	✓	✗	✗	✗	*	*
Uw vrijednosti	Ug = 1,1	1.34	/	1.34	/	/	/	/
	Ug = 1,0	1.28	/	1.28	/	/	/	/
	Ug = 0,9	/	1.21	/	1.21	1.19	1.14	1.07
	Ug = 0,8	/	1.14	/	1.14	1.12	1.07	1.01
	Ug = 0,7	/	1.07	/	1.07	1.05	1.01	0.94
	Ug = 0,6	/	1.01	/	1.01	0.98	0.94	0.87
	Ug = 0,5	/	0.94	/	0.94	0.91	0.80	0.78
Sigurnosni okovi	WK1	✓	✓	✓	✓	✓	✓	✓
	WK2	✓	✓	✓	✓	✓	✓	✓
Okov	Vidljivi	✓	✓	✓	✓	✓	✓	✗
	Skriveni do 80 kg nosivosti	✓	✓	✓	✓	✓	✗	✗
Brtve	Skriveni do 150 kg nosivosti Multipower	✗	✗	✗	✗	✗	✓	✓
	Q-Ion	✓	✓	✓	✓	✓	✓	✓
	EPDM	✓	✓	✓	✓	✓	✓	✓
	Silikon	✗	✗	✗	✗	✗	✗	✗

\* nije dostupno u sistemima sa poravnatim krilom i štokom prozora