

WOOD WINDOWS







Exclusive Classic
IV 68 mm

Exclusive Termic
IV 80 mm

Exclusive Passiv
IV 92 mm

		68	80	92
Profile dimensions (mm)	Installation depth	68	80	92
	Visible depth	118	112	112
	Visible width of horizontal transom	112	112	112
Construction options	Rectangular	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
	Oblique	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
	Arched, semicircular	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Opening options	Fixed	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
	Combined turn / tilt and turn	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
	Lift and slide doors	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
	Tilt and slide doors	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
	Folding doors	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
	Two-sided handle	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
	Opening outwards	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Thermal insulation Uw	Ug = 1,1	1.33	/	/
	Ug = 1,0	1.27	/	/
	Ug = 0,9	/	1.13	1.06
	Ug = 0,8	/	1.06	1.00
	Ug = 0,7	/	0.99	0.93
	Ug = 0,6	/	0.92	0.86
	Ug = 0,5	/	0.85	0.77
Security level	RC 1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
	RC2	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Hardware	Visible	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
	Hidden-to carry up to 80 kg	<input checked="" type="checkbox"/>	/	/
	Hidden-to carry up to 150 kg Multipower	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Gaskets	Q-Ion	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
	EPDM	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
	Silicon	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>

WOOD-ALUMINIUM WINDOWS



Premier Classic
DALU 68 mm

Premier Termic
DALU 68 mm

Premier Plus
DALU 68 mm

Premier Flat
DALU 68 mm

Premier Zero
DALU 68 mm

Premier Passiv
DALU 80 mm

Premier Passiv Modern
DALU 80 mm

	Premier Classic	Premier Termic	Premier Plus	Premier Flat	Premier Zero	Premier Passiv	Premier Passiv Modern	
Profile dimensions (mm)	Installation depth	82	78	78	78,5	78,5	93,5	110
	Visible depth	125	125	122	125	118	125	125
	Visible width of horizontal transom	80	80	✗	✗	80	80	80
Construction options	Rectangular	✓	✓	✓	✓	✓	✓	✓
	Oblique	✓	✓	✗	✓	✓	✓	✓
	Arched, semicircular	✓	✓	✗	✓	✗	✗	✗
Opening options	Fixed	✓	✓	✓	✓	✓	✓	✓
	Combined turn / tilt and turn	✓	✓	✓	✓	✓	✓	✓
	Lift and slide doors	✓	✓	✗	ZERO	✓	/	/
	Tilt and slide doors	✓	✓	✓	✓	✓	/	/
	Folding doors	✓	✓	✓	✓	✓	/	/
	Two-sided handle	✓	✓	✓	✓	✗	/	/
	Opening outwards	✓	✓	✗	✗	✗	*	*
Thermal insulation Uw	Ug = 1,1	1.34	/	1.34	/	/	/	/
	Ug = 1,0	1.28	/	1.28	/	/	/	/
	Ug = 0,9	/	1.21	/	1.21	1.19	1.14	1.07
	Ug = 0,8	/	1.14	/	1.14	1.12	1.07	1.01
	Ug = 0,7	/	1.07	/	1.07	1.05	1.01	0.94
	Ug = 0,6	/	1.01	/	1.01	0.98	0.94	0.87
	Ug = 0,5	/	0.94	/	0.94	0.91	0.80	0.78
Security level	RC 1	✓	✓	✓	✓	✓	✓	✓
	RC2	✓	✓	✓	✓	✓	✓	✓
Hardware	Visible	✓	✓	✓	✓	✓	✓	✗
	Hidden-to carry up to 80 kg	✓	✓	✓	✓	✓	✗	✗
	Hidden-to carry up to 150 kg Multipower	✗	✗	✗	✗	✗	✓	✓
Gaskets	Q-Ion	✓	✓	✓	✓	✓	✓	✓
	EPDM	✓	✓	✓	✓	✓	✓	✓
	Silicon	✗	✗	✗	✗	✗	✗	✗

* not available in sash/frame aligned aluminium systems