





WOOD-ALUMINIUM WINDOWS



Premier Classic
DALU 68 mm

Premier Termic
DALU 68 mm

Premier Plus
DALU 68 mm

Premier Flat
DALU 68 mm

Premier Zero
DALU 68 mm

Premier Passiv
DALU 80 mm

Premier Passiv Modern
DALU 80 mm

	Premier Classic	Premier Termic	Premier Plus	Premier Flat	Premier Zero	Premier Passiv	Premier Passiv Modern	
Profile dimensions (mm)	Installation depth	82	78	78	78,5	78,5	93,5	110
	Visible depth	125	125	122	125	118	125	125
	Visible width of horizontal transom	80	80	✗	✗	80	80	80
Construction options	Rectangular	✓	✓	✓	✓	✓	✓	✓
	Oblique	✓	✓	✗	✓	✓	✓	✓
	Arched, semicircular	✓	✓	✗	✓	✗	✗	✗
Opening options	Fixed	✓	✓	✓	✓	✓	✓	✓
	Combined turn / tilt and turn	✓	✓	✓	✓	✓	✓	✓
	Lift and slide doors	✓	✓	✗	ZERO	✓	/	/
	Tilt and slide doors	✓	✓	✓	✓	✓	/	/
	Folding doors	✓	✓	✓	✓	✓	/	/
	Two-sided handle	✓	✓	✓	✓	✗	/	/
	Opening outwards	✓	✓	✗	✗	✗	*	*
Thermal insulation Uw	Ug = 1,1	1.34	/	1.34	/	/	/	/
	Ug = 1,0	1.28	/	1.28	/	/	/	/
	Ug = 0,9	/	1.21	/	1.21	1.19	1.14	1.07
	Ug = 0,8	/	1.14	/	1.14	1.12	1.07	1.01
	Ug = 0,7	/	1.07	/	1.07	1.05	1.01	0.94
	Ug = 0,6	/	1.01	/	1.01	0.98	0.94	0.87
	Ug = 0,5	/	0.94	/	0.94	0.91	0.80	0.78
Security level	RC 1	✓	✓	✓	✓	✓	✓	✓
	RC2	✓	✓	✓	✓	✓	✓	✓
Hardware	Visible	✓	✓	✓	✓	✓	✓	✗
	Hidden-to carry up to 80 kg	✓	✓	✓	✓	✓	✗	✗
	Hidden-to carry up to 150 kg Multipower	✗	✗	✗	✗	✗	✓	✓
Gaskets	Q-Ion	✓	✓	✓	✓	✓	✓	✓
	EPDM	✓	✓	✓	✓	✓	✓	✓
	Silicon	✗	✗	✗	✗	✗	✗	✗

* not available in sash/frame aligned aluminium systems